



REVERSIBLE PLATE COMPACTOR



- 1 **Control handle** - provides steering leverage for easier handling, forward/reverse directional control through the double, two-directional exciters
- 2 **Lifting hook** for easy loading and unloading
- 3 **Wraparound steel engine protection with integral lifting bail**, gives the engine the protection it needs and offers a secure lifting point for transportation
- 4 **Honda powered** with either the reliable GX160 or GX270 engine
- 5 **Reversible Plate Compactor transportation wheels** for easy mobility around jobsite and storage (Optional)
- 6 **Heavy duty cast steel base plate** for a smooth quality finish and long life
- 7 **Extension Plates** which can be removed to use the Compactor Plate in narrow areas



| MODEL | ERPC150 | ERPC200 | ERPC300 |
|---|-------------------------|-------------------------|-----------------------------|
| PLATE SIZE (LxW) - in (mm) | 25.5 x 30.5 (650 x 500) | 27.6 x 23.4 (700 x 600) | 31.5 x 18.5 (800 x 470) |
| Extension Plate Size (LxW) - in (mm) | N/A | N/A | 31.5 x 25.2 (800 x 640) |
| Working Width - in (mm) / Extended - in (mm) | 30.5 (500) | 23.4 (600) | 18.5 (800) / ext 25.2 (640) |
| OPERATING WEIGHT - lbs (kg) | 304 (138) | 403 (183) | 661.5 (300) |
| WORKING SPEED - ft/min (m/min) | 72 (22) | 75.4 (23) | 72 (22) |
| VIBRATION FREQUENCY - vpm (Hz) | 5,400 (90) | 5,400 (90) | 4,200 (70) |
| CENTRIFUGAL FORCE - lbs (kN) | 6,745 (30) | 6,745 (30) | 8,992 (40) |
| COMPACTED AREA - ft ² /h (m ² /h) | 6997 (650) | 8,170 (759) | 8,525 (792) |
| FUEL TANK CAPACITY - qt (l) | 3.3 (3.1) | 5.6 (5.3) | 5.6 (5.3) |
| RUNNING TIME: hours | 2.2 | 4.6 | 4.6 |
| ENGINE | Honda GX160 | Honda GX270 | Honda GX270 |
| ENGINE TYPE | 4 - Stroke Gasoline | 4 - Stroke Gasoline | 4 - Stroke Gasoline |
| MAX. POWER OUTPUT - HP (kW) | 4.8 (3.6) | 8.5 (6.3) | 8.5 (6.3) |

1-800-417-9272 | ezgmfg.com
 1833 North Riverview Road
 Malta, OH | 43758

