SELF CONTAINED HEATER TRAILERS

PORTABLE HEAT AND POWER ANYWHERE YOU NEED IT



FVO-1000TR STANDARD EQUIPMENT

Two Flagro FVO-400HC Indirect Fired Heating Units 2 x 3500 lbs Dual Axle, 4 x 15" Galvanized Rims with Radial Tires Solid Steel Welded Channel Frame and Floor Electric Emergency Second Axle Brakes Duct Storage Cabinet Full Fuel Containment

FVO-400TRL STANDARD EQUIPMENT

One Flagro FVO-400HC Indirect Fired Heating Unit
3500 lbs Single Axle, 2 x 15" Galvanized Rims with Radial Tires
2 x 1000W Light Tower
Solid Steel Welded Channel Frame and Floor
Electric Emergency Brake
Full Fuel Containment



FVO-400TRL

SELF CONTAINED HEATER TRAILERS





Models	FVO-1000TR	FVO-400TRL
Heaters	2 x FVOHC-400 Flagro Indirect Fired Heaters	1 x FVOHC-400 Flagro Indirect Fired Heaters
Fuel Consumption	Engine- 1.08 GPH at full load	Engine- 1.08 GPH at full load
	Heaters - 2 x 390,000 BTU/hr @ 2.81 GPH each	Heaters - 1 x 390,000 BTU/hr @ 2.81 GPH
	44 hours run time before refueling	78 hours run time before refueling
Duct Cabinet	Included	N/A
Generators	Stamford Newage Generator	Stamford Newage Generator
	Single Phase - 120 V	Single Phase - 120 V
	Instrument Panel includes keyed ignition and	Instrument Panel includes keyed ignition
	hour meter	and hour meter
	8 kw @ 1800 rpm (14 HP)	8 kw @ 1800 rpm (14 HP)
Fuel Tanks	1100 liters / 299 US gallons	1100 liters / 299 US gallons
	Polythylene construction	Polythylene construction
	Fuel sight gauge and door	Fuel sight gauge and door
	4" fuel inlet nozzle mounted at the side of the	4" fuel inlet nozzle mounted at the side of
	trailers for ground access refueling	the trailers for ground access refueling
LxWxH	12' x 7'4" x 7'	12' x 7'4" x 7'
Weight	4000 lbs (empty)	2900 lbs (empty)
Light Tower		2 x 1000W lights
		9 ft - 2 stage mast
		Light bulb storage cabinet - standard
Approvals	CSA & ESA approved	CSA & ESA approved
	DOT approved trailer	DOT approved trailer



