



Husqvarna FS 627

Ideal for medium to small service and repair jobs when cutting concrete or asphalt.

Features Husqvarna FS 627

- Husqvarna's floor saws are robust, well designed and easy to use thanks to features as protective cage, lift bail and cutting depth indicator.
- Patent-pending raise/lower assist system, using gas spring.
- Raise/lower assist system Fully enclosed transmission. Lift bail is standard on all models. Dual arbors allow the blade to be mounted on either end of the bladeshaft for right or left cutting.

TECHNICAL SPECIFICATION	
Motor manufacturer	Kohler
Motor spec	CH740-0001
Max output (As rated by the engine manufacturer)	20 kW / 27 hp
Cylinders	2
Number of strokes	4-stroke engine
Cylinder displacement	44 cu. inch
Cylinder bore	3.3 inch
Cylinder stroke	2.64 inch
Fuel tank volume	5.25 gal.
Starter	Electric
Engine cooling	Air
Number of belts	4
Oil capacity, l	1.8 lit
Diamond blade, max	20"
Max cutting depth	7.625 inch
Blade depth control	Hydraulic
Blade shaft diameter	1.4375 inch
Blade flange	4"
Blade shaft RPM	2400 rpm
Arbor size	1"
Axle front	1 inch
Rear axle diameter	1 inch
Transmission type	Hydrostatic
Transmission speed	0-200 fpm
Handle bars	Multi position
Primary wheel size	Outside diameter: 6 Wheel width: 0 Inner bore: 0"
Secondary wheel size	Outside diameter: 10 Wheel width: 0 Inner bore: 0"
Blade guard type	Slip-on
Weight	650 lbs
Weight incl. packaging	723 lbs
Product size, LxWxH	39.5x25.5x39 inch

