

REPAIR KITS, UPGRADES, ACCESSORIES

DESCRIPTION	PART NUMBER	GP-1HD	GP-2HD	GP-3A	GP-6	GP-7	GP-8A
Repair Kit (1 diaphragm & 2 flapper valves)	5019-20	●	●				
Repair Kit (1 diaphragm & 2 flapper valves)	5019-37			●			
Repair Kit (2 diaphragms & 4 flapper valves)	5019-34				●	●	●
Pump Screw/Pivot Bushing Kit	5019-33	●	●				
3/4" ID Hose Reducer Kit x 5ft. long	5034	●	●	●	●		●
1" Hose Reducer Kit x 5ft. long	5083	●	●	●	●		●
1 1/2" ID Placement Hose x 5ft. long	5022-5ft	●	●	●	●		●
1 1/2" ID Placement Hose x 10ft. long	5022-10ft	●	●	●	●		●
1 1/2" ID Placement Hose x 15ft. long	5022-15ft	●	●	●	●		●
1 1/2" ID Placement Hose x 20ft. long	5022-20ft	●	●	●	●		●
1 1/2" Hose End, straight	5023	●	●	●	●		●
1 1/2" Hose End, 90 Elbow (L Shape)	5139	●	●	●	●		●
1 1/2" Hose End, 180 Elbow (J Shape)	5141	●	●	●	●		●
Metal Body Assembly Upgrade Kit	5019-38	●	●	●			
Metal Body Only Upgrade	5019-12M	●	●	●	●	●	●
Hi-Capacity Hopper Kit, 4.6 Gallon	5027	●					
Horizontal Handle Assembly	5019-1	●	●				
Remote Start/Stop Switch	Special Order			●			●

GP SERIES • LOW-PRESSURE GROUT PUMPS



CHOOSE FROM OUR SELECTION OF GP SERIES • LOW-PRESSURE GROUT PUMPS



Model	GP-1HD	GP-2HD	GP-3A	GP-6	GP-7	GP-8A	Model
Pump Type	Single Diaphragm	Single Diaphragm	Single Diaphragm	Twin Diaphragm	Twin Diaphragm	Twin Diaphragm	Pump Type
Power Source	Hand-Operated	Hand-Operated	Compressed Air	Hand-Operated	Hand-Operated	Compressed Air	Power Source
*Output Capacity	6 Gallons/Minute	6 Gallons/Minute	5 Gallons/Minute	11 Gallons/Minute	5 Gallons/Minute	9 Gallons/Minute	*Output Capacity
Output Pressure	0-15 PSI	0-15 PSI	15 PSI Maximum	0-15 PSI	0-15 PSI	18 PSI Maximum	Output Pressure
Hopper Capacity	1.9 Gallons	4.6 Gallons	4.6 Gallons	4.6 Gallons	4.6 Gallons	4.6 Gallons	Hopper Capacity
Placement Hose	1 1/2" ID x 60" Long	1 1/2" ID x 60" Long	1 1/2" ID x 60" Long	1 1/2" ID x 60" Long	1" ID x 72" Long	1 1/2" ID x 60" Long	Placement Hose
Discharge Head	10ft. Vertical Lift	10ft. Vertical Lift	10ft. Vertical Lift	10ft. Vertical Lift	10ft. Vertical Lift	10ft. Vertical Lift	Discharge Head
Dimensions	22 1/2" x 10" x 14 1/2" High	23 1/2" x 12" x 23" High	23 1/2" x 12" x 23" High	16 1/2" x 25" x 24" High	16 1/2" x 25" x 24" High	16 1/2" x 25" x 24" High	Dimensions
Net Weight	19 Pounds	21 Pounds	27 Pounds	32 Pounds	35 Pounds	38 Pounds	Net Weight
Remarks		Our most popular model!	Air Usage: Less than 3cfm. Controls include stop/start switch, speed control, pressure regulator & air gauge.		Used for door frames only. Fill both sides simultaneously.	Air Usage: Less than 6cfm. Controls include stop/start switch, speed control, pressure regulator & air gauge.	Remarks

* Output and performance will vary depending on the cycle rate, viscosity of grout mixture and pressure conditions.

* Output and performance will vary depending on the cycle rate, viscosity of grout mixture and pressure conditions.

FEATURES

- ✓ Choice of hand-operated or air-powered models
- ✓ Easy to operate, minimal maintenance required
- ✓ Pumps most types of cementitious grouts
- ✓ Lightweight & Portable; take the pump to where you need the pump
- ✓ Makes an ideal tool for placing grout anywhere that high pressure is not required

APPLICATIONS

- Grouting Metal Door & Window Frames • Filling Hollow Concrete Block
- Machine Base Grouting • Tilt-Up Panel Joint
- Waterproofing • Soil Stabilization
- Tank Stabilization • General Void Filling