

## HydraPaks ~ Gas & Dual-Output

### Gas & Dual Output HydraPak Features & Benefits

- ▶ Compact, lightweight hydraulic power source for RGC and other compatible hydraulic tools.
- ▶ Choose from models with Briggs & Stratton and Honda engines.
- ▶ Several models have variable flow and pressure settings.
- ▶ Cart-mounted with large 16 in. pneumatic tires.
- ▶ Low noise level. Much quieter than an air compressor.
- ▶ Easy maintenance and parts replacement.
- ▶ Controls easily accessible for safety and comfort.
- ▶ Electric start and low oil shutdown on all models.
- ▶ Powder-coated tubular steel frame protects unit from damage.
- ▶ Lifting eye and detachable handles for easy transporting and storage.
- ▶ 6 gallon oil reservoir and heavy duty 8-tube heat exchanger are standard on most models.
- ▶ HydraPaks with 18 hp Briggs & Stratton engines are equipped with an electronic governor.
- ▶ Dual-output HydraPaks can power two tools simultaneously.



**HV2312 Gas HydraPak**

- ▶ Extra heavy duty 10-tube heat exchanger, full set of gauges and a 6 gallon removable gas tank are standard on the HH2010, HV2310 and HV2312.

### Gas HydraPak Specifications

| Model         | HV1658                    | HV1858                    | HH2010   | HV2310   | HV2312   |
|---------------|---------------------------|---------------------------|--|--|--|
| Engine        | 16 hp B&S Vanguard        | 18 hp B&S Vanguard        | 20 hp Honda  | 23 hp B&S Vanguard   | 23 hp B&S Vanguard   |
| Fuel Capacity | 9 qt. (8.6 ltr)           | 9 qt. (8.6 ltr)           | 6 gal (22.7 ltr)   | 6 gal (22.7 ltr)   | 6 gal (22.7 ltr)   |
| Flow          | 5 or 8 gpm (20 or 30 lpm) | 5 or 8 gpm (20 or 30 lpm) | 0 - 10 gpm (0 - 38 lpm)  | 0 - 10 gpm (0 - 38 lpm)  | 0 - 12 gpm (0 - 45 lpm)  |
| Pressure      | 2250 psi (155 bar)        | 2250 psi (155 bar)        | 1750 psi (120 bar)<br>2000 psi (138 bar)<br>2500 psi (172 bar) | 2000 psi (138 bar)<br>2500 psi (172 bar)<br>3400 psi (231 bar) | 1750 psi (120 bar)<br>2000 psi (138 bar)<br>2500 psi (172 bar) |
| Hourometer    | Yes                       | Yes                       | Yes  | Yes  | Yes  |
| Weight        | 226 lbs (103 kg)          | 240 lbs (109 kg)          | 285 lbs (129 kg)   | 280 lbs (127 kg)   | 280 lbs (127 kg)   |



**HV1855 Dual-Output HydraPak**

### Dual-Output HydraPak Specifications

| Model         | HV1855                       | HV185510   |
|---------------|------------------------------|--|
| Engine        | 18 hp B&S Vanguard           | 18 hp B&S Vanguard                                       |
| Fuel Capacity | 9 qt. (8.6 ltr)              | 9 qt. (8.6 ltr)  |
| Flow          | Run 2 tools @ 5 gpm (20 lpm) | Run 2 tools @ 5 gpm (20 lpm) or 1 tool @ 10 gpm (38 lpm) |
| Pressure      | 2250 psi (155 bar)           | 2250 psi (155 bar)                                       |
| Hourometer    | Yes                          | Yes  |
| Weight        | 251 lbs (114 kg)             | 251 lbs (114 kg)   |





## HydraPaks ~ Bi-Directional & Electric

### Bi-Directional & Electric HydraPak Features & Benefits

- ▶ Compact, lightweight hydraulic power source for RGC and other compatible hydraulic tools.
- ▶ Cart-mounted with large 16 in. pneumatic tires.
- ▶ Low noise level. Much quieter than an air compressor.
- ▶ Easy maintenance and parts replacement.
- ▶ Controls are easily accessible for safety and comfort.
- ▶ Electric start and low oil shutdown on all models.
- ▶ Powder-coated tubular steel frame protects unit from damage.
- ▶ Lifting eye and detachable handles for easy transporting and storage.
- ▶ 6 gallon oil reservoir and heavy duty 8-tube heat exchanger on most models. HE1512 has a 10-tube heat exchanger.
- ▶ Full gauge set is standard on the HE1010 and HE1512.
- ▶ Electric HydraPaks are ideal for indoor work.
- ▶ Choose from 10 hp and 15 hp electric models.
- ▶ Contractors' choice for jobs in hospitals, schools, municipal buildings and other public facilities.
- ▶ Bi-Directional HydraPaks are designed for installing anchoring systems and similar jobs.



HV1858 Bi-Directional HydraPak



Motor Starter



HE1010 Electric HydraPak

### Bi-Directional HydraPak Specifications

| Model         | HH1358C                      | HV1658C                      | HV1858C                      |
|---------------|------------------------------|------------------------------|------------------------------|
| Engine        | 13 hp Honda                  | 16 hp B&S Vanguard           | 18 hp B&S Vanguard           |
| Fuel Capacity | 7 qt. (6.5 ltr)              | 9 qt. (8.6 ltr)              | 9 qt. (8.6 ltr)              |
| Flow          | 5 or 8 gpm<br>(20 or 30 lpm) | 5 or 8 gpm<br>(20 or 30 lpm) | 5 or 8 gpm<br>(20 or 30 lpm) |
| Pressure      | 2250 psi (155 bar)           | 2250 psi (155 bar)           | 2250 psi (155 bar)           |
| Hourmeter     | Yes                          | Yes                          | Yes                          |
| Weight        | 228 lbs (103 kg)             | 228 lbs (103 kg)             | 249 lbs (113 kg)             |

### Electric HydraPak Specifications

| Model                    | HE1058                       | HE1058                       | HE1010   | HE1010   | HE1512   | HE1512   |
|--------------------------|------------------------------|------------------------------|--|--|--|--|
| Motor                    | 10 hp Electric               | 10 hp Electric               | 10 hp Electric   | 10 hp Electric   | 15 hp Electric   | 15 hp Electric   |
| Electrical Requirements† | 208 - 220V,<br>3 Ph, 60 Hz   | 460V, 3 Ph, 60 Hz            | 208 - 220V,<br>3 Ph, 60 Hz                                     | 460V, 3 Ph, 60 Hz  | 208 - 220V,<br>3 Ph, 60 Hz   | 460V, 3 Ph, 60 Hz  |
| Flow                     | 5 or 8 gpm<br>(20 or 30 lpm) | 5 or 8 gpm<br>(20 or 30 lpm) | 0 - 10 gpm<br>(0 - 38 lpm)                                     | 0 - 10 gpm<br>(0 - 38 lpm)                                     | 0 - 12 gpm<br>(0 - 45 lpm)   | 0 - 12 gpm<br>(0 - 45 lpm)   |
| Pressure                 | 2250 psi (155 bar)           | 2250 psi (155 bar)           | 1750 psi (120 bar)<br>2000 psi (138 bar)<br>2500 psi (172 bar) | 1750 psi (120 bar)<br>2000 psi (138 bar)<br>2500 psi (172 bar) | 1750 psi (120 bar) *<br>2000 psi (138 bar) *<br>2500 psi (172 bar) † | 1750 psi (120 bar) *<br>2000 psi (138 bar) *<br>2500 psi (172 bar) † |
| Hourmeter                | Yes                          | Yes                          | Yes  | Yes  | Yes  | Yes  |
| Weight                   | 221 lbs (100 kg)             | 250 lbs (100 kg)             | 260 lbs (118 kg)   | 290 lbs (132 kg)   | 280 lbs (127 kg)   | 310 lbs (141 kg)   |

\* Continuous Duty Cycle † Intermittent Duty Only

