

Impact Wrenches and Drill

Impact Wrenches and 1/2" Drill

RGC's hydraulic Impact Wrenches and 1/2" Drill provide lightweight, quiet and efficient operation in a compact design. These tools are ideal for a variety of construction, municipal and utility applications.

Each tool is reversible. Two versions of the 7/16" wrench are available. One supplies 400 ft-lbs of torque at 8 gpm. The other wrench provides variable torque from 81 - 400 ft-lbs at 8 gpm. The 1" wrench requires an open-center system, while the other wrenches and drill change from open- to closed-center.


Contact RGC for information about other wrenches and drills with variable speed and torque settings.

Wrench and Drill Features & Benefits

- ▶ Durable, lightweight design reduces operator fatigue and increases productivity.
- ▶ Dual action spool on the 7/16" and 3/4" wrenches and drill provide operation on both open- and closed-center systems.
- ▶ Change from forward to reverse operation quickly and easily to save time and effort.
- ▶ Compact design allows use in confined work areas.
- ▶ All wrenches use a high torque motor.
- ▶ One of the 7/16" wrenches and the 3/4" wrench have adjustable torque controls.
- ▶ The 3/4" wrench is equipped with an auxiliary handle.



3/4 in. Impact Wrench



1 in. Impact Wrench



1/2 in. Drill

Impact Wrench and Drill Specifications

Model	7/16" Wrench	7/16" Wrench	3/4" Wrench	1" Wrench	1/2" Drill
Chuck Type	Hex Quick-Change	Hex Quick-Change	3/4" Square Drive	1" Square Drive	1/2" Key
Pressure	1000 - 2000 psi (69 - 140 bar)	1000 - 2000 psi (69 - 140 bar)	1000 - 2000 psi (69 - 138 bar)	2000 psi (138 bar)	1000 - 2000 psi (69 - 138 bar)
Flow	4 - 10 gpm (15 - 38 lpm)	4 - 10 gpm (15 - 38 lpm)	4 - 12 gpm (15 - 45 lpm)	10 gpm (38 lpm)	4 - 8 gpm (15 - 30 lpm)
Back Pressure (max.)	200 psi (13.8 bar)	200 psi (13.8 bar)	200 psi (13.8 bar)	200 psi (13.8 bar)	200 psi (13.8 bar)
Operation	Open- or Closed-Center	Open- or Closed-Center	Open- or Closed-Center	Open-Center	Open- or Closed-Center
Torque	400 ft-lb @ 8 gpm (542 Nm @ 30 lpm)	80 - 400 ft-lb (108 - 542 Nm)	1060 ft-lb @ 6 gpm 1437 Nm @ 23 lpm)	Up to 2500 ft-lb (up to 3390 Nm)	N/A
Dimensions (H x W x L)	10 6" x 4 2" x 8 2" (26.9 x 10.7 x 20.8 cm)	10 6" x 4 2" x 8 2" (26.9 x 10.7 x 20.8 cm)	11 7" x 3 8" x 9 7" (29.7 x 9.5 x 24.6 cm)	12" x 4" x 16" (30.5 x 10.1 x 40.6 cm)	9" x 3" x 7 5" (22.9 x 7.6 x 19.1 cm)
Weight (approx.)	7.4 lbs. (3.4 kg)	7.7 lbs. (3.5 kg)	12.3 lbs. (5.6 kg)	24 lbs. (10.9 kg)	6 lbs. (2.7 kg)

