LOWRIDER POWERTROWEL



0



LOWRIDER POWER TROWELS



With 3 sizes, 6 distinctly different models and manual or hydraulic steering, MBW **LOWRIDERS** cover the full range of floating and finishing applications. LOWRIDERS have been in production for over 25 years and played an important role in the pioneering and development of riding trowels. Decades of experience has resulted in the industry's lowest maintenance line of high performance ride-on trowels. LOWRIDERS are simple machines with far fewer moving parts, the industry's most reliable drive train, the highest quality components and materials. LOWRIDERS set industry standards for high performance, low maintenance and long life.

MK8-75 is the industry's smallest ride-on trowel. Perfect for large or small jobs, multi-story flooring and as a compliment to large machines that just can't operate in tight areas. This 468 lb. rider transports in the bed of a pick-up, passes through a 32" doorway, can be used as an edging trowel. Floats and finishes with equal proficiency.

MK8-90 is a manual steer, 20 hp, 6 foot machine. Excellent for float or finish applications with a low center of gravity for improved operating stability. A clean, easy to service design. A workhorse on typical applications.

MK8-91 is the industry's only hydraulic steer, 25 hp, 6 foot machine. Same basic design as MK8-90, but hydraulic steering reduces operator fatigue on long duration applications.

MK8-120 is a manual steer, 31 hp, 8 foot machine. Our most popular North American model. Low center of gravity, superior lines of sight, protected drive train and easy to service. Another workhorse in floating or finishing applications.

MK8-121 is the hydraulic steer version of the MK8-120 with choice of a gas or diesel engine. Low center of gravity, ease of operation and service. A low maintenance, long lived product.

SPECIFICATIONS	MK8-75H	MK8-90	MK8-91	MK8-120	MK8-121	MK8-121
Engine	Honda GX390 (389 cm³)	Kohler Command PRO 20	Kohler Command PRO 25	Briggs & Stratton Vanguard 31	Briggs & Stratton Vanguard 35	Kubota D902
Operating Weight	468 lbs (212 kg)	635 lbs (288 kg)	789 lbs (357 kg)	704 lbs. (319 kg)	872 lbs. (395 kg)	1115 lbs. (506 kg)
Blades	8	8	8	8	8	8
Troweling Path	63 in (161 cm)	76 in (194 cm)	76 in (194 cm)	100 in (254 cm)	100 in (254 cm)	100 in (254 cm)
Fuel	Gasoline	Gasoline	Gasoline	Gasoline	Gasoline	Diesel
Steering	Manual	Manual	Hydraulic	Manual	Hydraulic	Hydraulic
Rotors	2	2	2	2	2	2
Rotor Speeds	up to 130 rpm	up to 125 rpm	up to 125 rpm	up to 125 rpm	up to 125 rpm	up to 125 rpm

() Metric Measurements. Specifications subject to change without notice.



MBW Inc.

250 Hartford Road • P.O. Box 440 Slinger, Wisconsin • 53086-0440 • USA Ph: 800-678-5237 or 262-644-5234 • Fax: 262-644-5169 E-mail: mbw@mbw.com • Website: www.mbw.com

MBW UK Ltd.

Units 2 & 3 Cochrane Street • Bolton BL3 6BN • England UK Ph: 44 (0) 1204 387784 • Fax: 44 (0) 1204 387797 E-mail: mbwuk@btinternet.com • Website: www.mbw.com

MBW FRANCE S.A.R.L.

Z.A. d'Outreville • 5 rue Jean Baptiste Néron • 60540 BORNEL • France Ph: 33 (0) 3 44 07 15 96 • Fax: 33 (0) 3 44 07 41 28 E-mail: mbwfrance@free.fr • Website: www.mbw.com

AUTHORIZED DISTRIBUTOR

L16482 01/13 Copyright© MBW Incorporated All Rights Reserved